MAZAKA
HEAVY INDUSTRY

ASPHALT CRACK FILLING EQUIPMENT

DRAGON



MAZAKA
HEAVY INDUSTRY

ASPHALT CRACK FILLING EQUIPMENT
DRAGON D8/D10









TECHNICAL SPECIFICATIONS

	DRAGON D8	DRAGON D10
Fuid Capacity	30 lt.	47 lt.
Steel Thickness	2 mm	2 mm
Fuel Type	Propane	Propane
Fuel Pressure	2 bar	2 bar
Agitation Type	Manuel	Manuel
Weight	54 kg	60 kg
Widht (A)	600 mm	600 mm
Height (B)	900 mm	900 mm
Lenght (C)	1200 mm	1200 mm





- Rapidly melts hot rubberized crack sealant, bringing the material quickly to application-ready condition.
- Allows walking-speed application, enabling fast crack repair over large areas.
- Compact design allows easy transport by vehicle and quick setup on site.
- Height-adjustable operator handle for improved ergonomics and control.
- High-sealing performance safety valve for safe and reliable operation.
- Powerful propane burner system heats the sealant to working temperature in a short time.
- Balanced heat distribution ensures uniform and consistent melting of the material.
- Melting and application can be easily performed by a single operator.
- Industrial-grade components minimize maintenance requirements and ensure long service life.

05.03.26 / REV. NO 01

Mazaka Factory
Mimarsinan OSB Mah. 7. Cadde No:24
Melikgazi/Kayseri/TÜRKİYE
+90 352 311 44 18 +90 533 204 41 70
info@mazaka.eu

Mazaka USA LLC
2611 Andjon Drive
Dallas, TX 75220
+1 203 904 8074
america@mazaka.eu

Mazaka Europe Office
Industriestrasse 12-16, 42929
Wermelskirchen Germany
+90 553 468 13 24
europe@mazaka.eu

www.mazaka.eu